





MODEL	WIDTH "A"	STRUCK VOLUME	HEAPED VOLUME	WEIGHT
MT36	36"	5 1/2 FT <sup>3</sup>	7 FT <sup>3</sup>	420 LBS
MT42	42"	6 1/4 FT³	8 FT³	440 LBS
MT44	44"	6 3/4 FT <sup>3</sup>	8 1/2 FT <sup>3</sup>	450 LBS
MT48	48"	7 1/4 FT³	9 3/8 FT <sup>3</sup>	470 LBS
MT54	54"	8 FT³	10 1/2 FT <sup>3</sup>	490 LBS
MT60	60"	9 FT³	12 FT³	510 LBS

## **FEATURES**

- MADE WITH AR400, AR200, AND GRADE 50 MATERIAL
- 5" BALL BEARINGS THAT ARE TRIPLE SEALED TO PROTECT FROM THE ELEMENTS.
- •2 CUTTING EDGES LEADING UP TO THE DRUM TO SHRED ANYTHING TRYING TO GET THROUGH.
- ◆6,700 IN/LB CHAR-LYNN HYDRAULIC MOTOR HOUSED INSIDE THE DRUM FOR ULTIMATE PROTECTION.
  - CAPABLE OF HANDELING 20GPM OF HYDRAULIC FLOW
    - ULTRA HARD CARBIDE CUTTER TEETH ON DRUM.
- ullet GET ADDITIONAL CONTROL FROM THE DIRECT-DRIVE AND POWERFUL MOTOR WHICH ONLY PROTRUDES 2.5" BEYOND THE SIDE PLATE.
  - CROSSOVER RELIEF VALVES TO HELP DAMPEN SHOCK TO THE HYDRAULIC SYSTEM.
    - COMPLETELY FABRICATED IN OUR FACILITY IN CLEAR LAKE MINNESOTA.